

中国总代理: Nano 电子商城

电话:4006609565 19mro@19mro.com

http://www.19mro.com

FOMBLIN(R) Y HVAC 全氟聚醚润滑油 MSDS

1.PRODUCT AND COMPANY IDENTIFICATION

1.1. Identification of the substance or mixture

产品名称 : FOMBLIN(R) Y HVAC

等级 : VAC 18/8; VAC 25/9; VAC 40/11; VAC 140/13

分子式 CF3-O-(C3F6-O)n-(CF2-O)m-CF3

:

摩尔质量 2,500 - 6,500

1.2. Use of the Substance/Mixture

推荐使用 : - Lubricant

Electronic industryElectrical industryChemical industryFor industrial use only.

1.3. 制造商

Address : SOLVAY SPECIALTY POLYMERS USA, LLC

4500 McGINNIS FERRY ROAD ALPHARETTA GA 30005-3914

United States

1.4. 紧急联系电话

Emergency telephone : 1 (800) 424-9300 CHEMTREC ® (USA & Canada)

number

Contact telephone number

(product information):

: (856) 853-8119 (Product information)

2.HAZARDS IDENTIFICATION

2.1. Emergency Overview:

NFPA : H= 1 F= 0 I= 0

General Information

Appearance : liquid
Colour : colourless
Odour : odourless

Main effects

The product is biologically inert.

Not hazardous in normal conditions of handling and use

Ecological injuries are not known or expected under normal use.

- Thermal decomposition can lead to release of toxic and corrosive gases.

2.2. Potential Health Effects:



Inhalation

No known effect.

Eye contact

- Contact with eyes may cause irritation.
- Redness

Skin contact

Redness

Ingestion

- Ingestion may provoke the following symptoms:
- Symptoms: Nausea, Vomiting, Diarrhoea.

Other toxicity effects

- See section 11: Toxicological Information

2.3. Environmental Effects:

- See section 12: Ecological Information

3.COMPOSITION/INFORMATION ON INGREDIENTS

1-Propene, 1,1,2,3,3,3-hexafluoro-, oxidized, polymd.

4.FIRST AID MEASURES

4.1. Inhalation

- Move to fresh air in case of accidental inhalation of fumes from overheating or combustion.
- Oxygen or artificial respiration if needed.

4.2. Eye contact

- Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
- If eye irritation persists, consult a specialist.

4.3. Skin contact

- Wash off with soap and water.
- If symptoms persist, call a physician.

4.4. Ingestion

- Drink 1 or 2 glasses of water.
- Do NOT induce vomiting.
- If symptoms persist, call a physician.

5.FIRE-FIGHTING MEASURES

5.1. Suitable extinguishing media

- Water
- powder
- Foam
- Dry chemical
- Carbon dioxide (CO2)

5.2. Extinguishing media which shall not be used for safety reasons

- None.
- 5.3. Special exposure hazards in a fire

- The product is not flammable.
- Not explosive
- In case of fire hazardous decomposition products may be produced such as: Gaseous hydrogen fluoride (HF),
 Fluorophosgene

5.4. Hazardous decomposition products

- Gaseous hydrogen fluoride (HF).
- Fluorophosgene

5.5. Special protective equipment for fire-fighters

- Wear self-contained breathing apparatus and protective suit.
- When intervention in close proximity wear acid resistant over suit.

5.6. Other information

- Evacuate personnel to safe areas.
- Approach from upwind.
- Protect intervention team with a water spray as they approach the fire.
- Keep containers and surroundings cool with water spray.
- Keep product and empty container away from heat and sources of ignition.

6.ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions

- Ensure adequate ventilation.
- Material can create slippery conditions.
- Sweep up to prevent slipping hazard.
- Prevent further leakage or spillage if safe to do so.
- Keep away from open flames, hot surfaces and sources of ignition.
- Refer to protective measures listed in sections 7 and 8.

6.2. Environmental precautions

- Should not be released into the environment.
- The product should not be allowed to enter drains, water courses or the soil.
- In case of accidental release or spill, immediately notify the appropriate authorities if required by Federal, State/Provincial and local laws and regulations.

6.3. Methods for cleaning up

- Soak up with inert absorbent material.
- Suitable material for picking up
- Dry sand
- Earth
- Shovel into suitable container for disposal.

7.HANDLING AND STORAGE

7.1. Handling

- No special handling advice required.
- Ensure adequate ventilation.
- Use personal protective equipment.
- Keep away from heat and sources of ignition.
- To avoid thermal decomposition, do not overheat.
- Take measures to prevent the build up of electrostatic charge.
- Clean and dry piping circuits and equipment before any operations.
- Ensure all equipment is electrically grounded before beginning transfer operations.

7.2. Storage

- No special storage conditions required.
- Keep away from heat and sources of ignition.
- Keep in properly labelled containers.
- Keep away from combustible material.
- Keep away from incompatible products

7.3. Packaging material

Plastic material PP, PE, PVDF, PTFE, PFA.

7.4. Other information

- Provide tight electrical equipment well protected against corrosion.
- Refer to protective measures listed in sections 7 and 8.

8.EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Exposure Limit Values

Remarks:

- Threshold limit values of by-products from thermal decomposition

Hydrogen fluoride anhydrous

US. ACGIH Threshold Limit Values 2009

time weighted average = 0.5 ppm

Remarks: as F

US. ACGIH Threshold Limit Values 2009

Ceiling Limit Value = 2 ppm

Remarks: as F

US. OSHA Table Z-1-A (29 CFR 1910.1000) 1989

time weighted average = 3 ppm

Remarks: as F

US. OSHA Table Z-1-A (29 CFR 1910.1000) 1989

Short term exposure limit = 6 ppm

Remarks: as F

US. ACGIH Threshold Limit Values 2009

Remarks: as F, Can be absorbed through skin.

- US. OSHA Table Z-2 (29 CFR 1910.1000) 02 2006

time weighted average = 3 ppm

- US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) 02 2006

Permissible exposure limit = 2.5 mg/m3

Remarks: as F

- US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A 06 2008

time weighted average = 3 ppm

Remarks: as F

- US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A 06 2008

Short term exposure limit = 6 ppm

Remarks: as F

Carbonyl difluoride

US. ACGIH Threshold Limit Values 2009

time weighted average = 2 ppm

US. ACGIH Threshold Limit Values 2009

Short term exposure limit = 5 ppm

US. OSHA Table Z-1-A (29 CFR 1910.1000) 1989

time weighted average = 2 ppm

time weighted average = 5 mg/m3

- US. OSHA Table Z-1-A (29 CFR 1910.1000) 1989

Short term exposure limit = $5 \overline{ppm}$

Short term exposure limit = 15 mg/m3

US. OSHA Table Z-2 (29 CFR 1910.1000) 02 2006

time weighted average = 2.5 mg/m3

Remarks: Dust

- US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) 02 2006

Permissible exposure limit = 2.5 mg/m3

Remarks: as F

- US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A 06 2008

time weighted average = 2 ppm time weighted average = 5 mg/m3

- US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A 06 2008

Short term exposure limit = 5 ppm

Short term exposure limit = 15 mg/m3

ACGIH® and TLV® are registered trademarks of the American Conference of Governmental Industrial Hygienists.

SAEL = Solvay Acceptable Exposure Limit, Time Weighted Average for 8 hour workdays. No Specific TLV STEL (Short Term Exposure Level) has been set. Excursions in exposure level may exceed 3 times the TLV TWA for no more than a total of 30 minutes during a workday and under no circumstances should they exceed 5 times the TLV TWA.

8.2. Engineering controls

- Provide local ventilation appropriate to the product decomposition risk (see section 10).
- Refer to protective measures listed in sections 7 and 8.
- Apply technical measures to comply with the occupational exposure limits.
- For additional information, consult the current edition of The Guide to the Safe Handling of Fluoropolymers published by the Society of Plastics Industry, Inc. (SPI) Fluoropolymer Division.

8.3. Personal protective equipment

8.3.1. espiratory protection

- No personal respiratory protective equipment normally required.
- Wear self-contained breathing apparatus in confined spaces, in cases where the oxygen level is depleted, or in case of significant emissions.
- Use only respiratory protection that conforms to international/ national standards.
- Use NIOSH approved respiratory protection.
- Comply with OSHA respiratory protection requirements.

8.3.2. and protection

- Rubber or plastic gloves
- Latex gloves
- Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

8.3.3. ye protection

- Safety glasses with side-shields
- If splashes are likely to occur, wear: Tightly fitting safety goggles

8.3.4. kin and body protection

- Lab coat
- Long sleeved clothing

8.3.5. ygiene measures

- Ensure that eyewash stations and safety showers are close to the workstation location.
- When using do not eat, drink or smoke.
- Wash hands before breaks and at the end of workday.
- Handle in accordance with good industrial hygiene and safety practice.

9.PHYSICAL AND CHEMICAL PROPERTIES

9.1. General Information

Appearance: liquidColour: colourlessOdour: odourless

9.2. Important health safety and environmental information

Boiling point/boiling range : $> 270 \, ^{\circ}\text{C} \, (518 \, ^{\circ}\text{F})$

Flash point : Remarks: The product is not flammable.
Flammability : Remarks: The product is not flammable.

Explosive properties : Explosion danger.

Remarks: Not explosive

Oxidizing properties : Remarks: Non oxidizer

Vapour pressure : < 0.0000001 hPa

Temperature: 20 °C (68 °F)

Relative density / Density : 1.89 - 1.92 g/cm3

Solubility(ies) : Water

Remarks: insoluble fluorinated solvents Remarks: soluble

Viscosity : 283.5 - 3,264 mPa.s

9.3. Other data

Melting point/range : Remarks: not applicable

Decomposition : > 290 °C (554 °F)

temperature

10. STABILITY AND REACTIVITY

10.1. Stability

Stable under recommended storage conditions.

10.2. Conditions to avoid

- To avoid thermal decomposition, do not overheat.
- Keep away from flames and sparks.
- Keep at temperature not exceeding: 290 °C (554 °F)

10.3. Materials to avoid

 Combustible material, Flammable materials, non-aqueous alkalis, Lewis acids (Friedel-Crafts) above 100°C, Aluminum and magnesium in powder form above 200°C, metals promote and lower decomposition temperature

10.4. Hazardous decomposition products

- Gaseous hydrogen fluoride (HF)., Fluorophosgene

11.TOXICOLOGICAL INFORMATION

Toxicological data

Acute oral toxicity

LD50, rat, > 15,000 mg/kg

Acute dermal irritation/corrosion

LD50, rat, > 5,000 mg/kg

Skin irritation

- rabbit. No skin irritation
- rabbit. No skin irritation

Eve irritation

rabbit, No eye irritation

Sensitisation

- guinea pig, Did not cause sensitization on laboratory animals.

Genetic toxicity in vitro

- Not mutagenic in Ames Test.
- negative, Remarks: Chromosome aberration test in vitro

Remarks

- Description of possible hazardous to health effects is based on experience and/or toxicological characteristics of several components.
- The product is biologically inert.
- Thermal decomposition can lead to release of toxic and corrosive gases.
- Exposure to decomposition products
- Causes severe irritation of eyes, skin and mucous membranes.

12.ECOLOGICAL INFORMATION

12.1. Ecotoxicity effects

Acute toxicity

- Fishes, Brachydanio rerio, LC50, 96 h, > 360 mg/l
 - Remarks: saturated aqueous solution
- Daphnia magna (Water flea), EC50, 48 h, > 360 mg/l

Remarks: saturated aqueous solution

12.2. Mobility

Remarks: no data available

12.3. Persistence and degradability

Abiotic degradation

Result: no data available

Biodegradation

Remarks: no data available

12.4. Bioaccumulative potential

- Result: no data available

12.5. Other adverse effects

no data available

12.6. Remarks

- Ecological injuries are not known or expected under normal use.

13.DISPOSAL CONSIDERATIONS

13.1. Waste from residues / unused products

- Do not dump into any sewers, on the ground, or into any body of water. All disposal methods must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations.
- Waste characterizations and compliance with applicable laws and regulations are the responsibility of the waste generator.
- Can be incinerated, when in compliance with local regulations.
- The incinerator must be equipped with a system for the neutralisation or recovery of HF.

13.2. Packaging treatment

Empty containers can be landfilled, when in accordance with the local regulations.

13.3. RCRA Hazardous Waste

- Listed RCRA Hazardous Waste (40 CFR 302) - No

14.TRANSPORT INFORMATION

- Sea (IMO/IMDG)
- not regulated
- Air (ICAO/IATA)
- not regulated
- U.S. Dept of Transportation
- not regulated
- It is recommended that ERG Guide number 111 be used for all non-regulated material.
- Canadian Transportation of Dangerous Goods
- not regulated

15.REGULATORY INFORMATION

15.1. Inventory Information

Toxic Substance Control Act list (TSCA)	:	-	In compliance with inventory.
Australian Inventory of Chemical Substances (AICS)	:	-	In compliance with inventory.
Canadian Domestic Substances List (DSL)	:	-	In compliance with inventory.
Inventory of Existing Chemical Substances (China) (IECS)	:	-	In compliance with inventory.
Korean Existing Chemicals Inventory (KECI (KR))	:	-	In compliance with inventory.
Japanese Existing and New Chemical Substances (MITI List) (ENCS)	:	-	In compliance with inventory.
New Zealand Inventory (in preparation) (NZ)	:	-	In compliance with inventory.
Philippine Inventory of Chemical and Chemical Substances (PICCS)	:	-	In compliance with inventory.
EU list of existing chemical substances (EINECS)	:	-	not applicable, Product falls under the EU-polymer definition

15.2. Other regulations

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

- not regulated.

SARA Hazard Designation (SARA 311/312)

- Acute Health Hazard: No.
- Chronic Health Hazard: No.
- Fire Hazard: No.
- Reactivity Hazard: No.
- Sudden Release of Pressure Hazard: No.

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 313 Toxic Chemicals (40 CFR 372.65) - Supplier Notification Required

- not regulated.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not regulated.

US. New Jersey Worker and Community Right-to-Know Act (New Jersey Statute Annotated Section 34:5A-5)

not regulated.

US. Pennsylvania Worker and Community Right-to-Know Law (34 Pa. Code Chap. 301-323)

not regulated.

US. California Safe Drinking Water & Toxic Enforcement Act (Proposition 65)

- This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm..

OSHA Hazard communication standard

This material is non-hazardous as defined by the American OSHA Hazard Communication Standard.

15.3. Classification and labelling

Canada. Canadian Environmental Protection Act (CEPA). WHMIS Ingredient Disclosure List (Can. Gaz., Part II, Vol. 122, No. 2)

NOCONTPROD - Does not contain a controlled product

Remarks: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

EC Label

- Substance non classified according to Directive 67/548/EEC.

16.OTHER INFORMATION

Ratings:

NFPA (National Fire Protection Association)

Health = 1 Flammability = 0 Instability = 0

Further information

- New (MSDS)

Distribute new edition to clients

Material Safety Data Sheets contain country specific regulatory information; therefore, the MSDS's provided are for use only by customers of the company mentioned in section 1 in North America. If you are located in a country other than Canada, Mexico or the United States, please contact the Solvay Group company in your country for MSDS information applicable to your location.

The previous information is based upon our current knowledge and experience of our product and is not exhaustive. It applies to the product as defined by the specifications. In case of combinations or mixtures, one must confirm that no new hazards are likely to exist. In any case, the user is not exempt from observing all legal, administrative and regulatory procedures relating to the product, personal hygiene, and integrity of the work environment. (Unless noted to the contrary, the technical information applies only to pure product).

To our actual knowledge, the information contained herein is accurate as of the date of this document. However, neither the company mentioned in section 1 nor any of its affiliates makes any warranty, express or implied, including merchantability or fitness for use, or accepts any liability in connection with this information or its use. This information is for use by technically skilled persons at their own discretion and risk and does not relate to the use of this product in combination with any other substance or any other process. This is not a license under any patent or other proprietary right. The user alone must finally determine suitability of any information or material for any contemplated use in compliance with applicable law, the manner of use and whether any patents are infringed. This information gives typical properties only and is not to be used for specification purposes. The company mentioned in section 1 reserves the right to make additions, deletions or modifications to the information at any time without prior notification.

Trademarks and/or other products of the company mentioned in section 1 referenced herein are either trademarks or registered trademarks of the company mentioned in section 1 or its affiliates, unless otherwise indicated.

Copyright 2009, Company mentioned in Section 1. All Rights Reserved.